



**NORMALLY CLOSED**  
**PORT SIZE: 1/2" N.P.T.**  
**MAX OPERATING PRESSURE: 230 PSI (15 bar)**  
**OPERATING TEMPERATURE: 14°F (-10°C) TO 140° (60°C)**  
**VAC POWER REQUIREMENTS: 120/60, 110/50, 240/60, 220/50**  
**VDC POWER REQUIREMENTS: 12, 24**  
**7 WATT (DC)**  
**7 WATT (AC)**  
**INGRESS PROTECTION: IP65**  
**BODY MATERIAL: BRASS**  
**WEIGHT: 0.84LBS (0.38 KG)**  
**REBUILD KIT #323457**

**CONFIDENTIAL**

INFORMATION CONTAINED HEREIN IS CONFIDENTIAL. IT IS THE PROPERTY OF KAHLBERG INDUSTRIES INC. IT IS TO BE USED SOLELY FOR THE PURPOSE PROVIDED, AND IT IS NOT TO BE DISCLOSED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF KAHLBERG INDUSTRIES INCORPORATED.

**Kahlberg**  
 KAHLBERG INDUSTRIES INC. TWO RIVERS, WISCONSIN 54241

**OUTLINE DIMENSIONS**  
**V-151D SOLENOID VALVE**

DR.	DATE	CKD.	SCALE	DRWG. NO.	REV.
ZJN	03/11/16	EMK	N.T.S.	3-7031	