


REV.	BY	DATE	DESCRIPTION	APP'D.



NOTES:

- 1) ALL PIPING SHOULD SLOPE TO AN ACCESSIBLE MOISTURE DRAIN POINT. IT IS RECOMMENDED THAT ADDITIONAL MOISTURE TRAPS BE PLACED AT THE BOTTOM OF ALL VERTICAL PIPING RUNS.
- 2) THE MAIN AIR LINE FROM AIR RECEIVER TO HORN MUST BE OF ADEQUATE DIAMETER TO MINIMIZE FRICTION LOSS OF PRESSURE IN AIR LINE. CONTACT KAHLBERG INDUSTRIES IF ASSISTANCE IS NEEDED.
- 3) CHECK ALL PIPING AND FITTINGS REGULARLY TO AVOID LEAKS IN THE SYSTEM, FILTERS, REGULATORS AND OTHER ACCESSORIES SHOULD ALSO BE PROPERLY MAINTAINED.
- 4) PIPING RUNS SHOWN ARE SCHEMATIC ONLY.
- 5) THIS DRAWING IS INTENDED TO BE USED IN CONJUNCTION WITH THE COMPLETE INSTRUCTION MANUAL FOR MODEL KC-6 SERIES COMPRESSORS (SHIPPED WITH COMPRESSOR SYSTEM).
- 6) AFTER THE P563-02 REGULATOR, ALL PIPING, SOLENOID VALVE, AND AIR HORN ARE SHOWN FOR REFERENCE ONLY, AND ARE NOT SUPPLIED WITH THE M-189 AIR RECEIVER KIT.

ITEM	PART #	DESCRIPTION	QTY.
1	PT134-021	REDUCER BUSHING, 1-1/4" TO 3/4" N.P.T., CAST IRON	2
2	PT134-001	REDUCER BUSHING, 3/4" TO 1/2" N.P.T., BRASS	1
3	P516-12	CONNECTOR, QUICK CONNECT, 1/2" N.P.T. TO 3/8" TUBE	1
4	PT130-009	TUBE, ANION, BLACK, 3/8" O.D.	15
5	M-189	AIR RECEIVER, ASME STEEL, PRIMER FINISHED, 30 GALLON	1
6	P127-04	PIPE PLUG, BRASS, 1/2"	2
7	V-49C	SAFETY RELIEF VALVE, BRASS, 200 P.S.I. SETTING	1
8	M-141B	AIR GAGE, 1-1/4" N.P.T., CENTER BACK MOUNT	1
9	P129-04	PIPE, BRASS, 3/4" X 1-1/2"	1
10	D179-02	REGULATOR, AIR PRESSURE, 3/4" N.P.T.	1
11	P563-03	SOLENOID VALVE, 1/4" N.P.T., FEMALE X FEMALE, BRASS	1
12	V-122	BALL VALVE, 3/4" N.P.T., FEMALE X FEMALE, BRASS	1
13	M-101	AIR STRAINER, MOISTURE TRAP, BRASS, 3/4" N.P.T.	1



INSTALLATION/PARTS LIST
M-189 AIR RECEIVER KIT

DR.	DATE	CKD.	SCALE	DRWG. NO.	REV.
EMK	09-26-19	EMK	N.T.S.	3-7413	-