

Explosion Proof Solenoid Valves

These normally closed explosion-proof solenoid valves are ideal for industrial and marine use, and are specifically selected for use with certain Kahlenberg Horns based on air flow requirements. These valves are available in sizes 3/8" to 1-1/4" NPT, and A.C. or D.C. Voltages as indicated below.



Technical Details:

- 3/8" to 1-1/4" Female NPT
- Normally closed, explosion proof watertight coil
- Maximum operating air pressure: 200 PSI.
- Power Consumption: 6.1 Watts on 60 Hz, 16 VA holding, 40 VA inrush.
- Material: body - brass, elastomer - Buna N.
- UL and CSA Class 1, Div 1 group A,B,C and D. Class 2 Div 1 group E, F & G.
- Nema 3, 3S, 4, 4X, 6, 6P, 7 & 9.

Part Number	Size	Voltage
10905	3/8" N.P.T.	230 V.A.C. 50/60 Hz
10906	3/8" N.P.T.	120 V.A.C. 50/60 Hz
10907	3/8" N.P.T.	12 V.D.C.
10908	3/8" N.P.T.	24 V.D.C.
10910	1/2" N.P.T.	120 V.A.C. 50/60 Hz
10911	1/2" N.P.T.	12 V.D.C.
10912	1/2" N.P.T.	24 V.D.C.
10946	1/2" N.P.T.	230 V.A.C. 50/60 Hz
10914	3/4" N.P.T.	120 V.A.C. 50/60 Hz
10915	3/4" N.P.T.	230 V.A.C. 50/60 Hz
10916	3/4" N.P.T.	12 V.D.C.
10917	3/4" N.P.T.	24 V.D.C.
10919	1-1/4" N.P.T.	120 V.A.C. 50/60 Hz
10920	1-1/4" N.P.T.	230 V.A.C. 50/60 Hz

Kahlenberg Industries, Inc.

1700 12th Street, P.O. Box 358
Two Rivers, Wisconsin, 54241

Phone: (920) 793-4507 / Fax: (920) 793-1346

Website: www.kahlenberg.com Email: info@kahlenberg.com