

### Model RCP20H Air Compressor

The Model RCP20H Air Compressor is a simple, durable, 2 HP, 20 gallon single stage compressor system for use with Kahlenberg industrial signaling devices



#### TECHNICAL DATA

Single Stage Stationary Electric Simplex Design

2 H.P, 115/230 Volt 1Ph. A.C.

7.11 C.F.M. Air Delivery at 100 p.s.i., Max 130 p.s.i.

20 Gallon ASME Vertical Air Receiver

Start/Stop Pressure Switch Set at 110 p.s.i. cut in, 130 p.s.i. cut out

Fully Enclosed Beltguard, ASME Safety Valve, Tank Drain and discharge valve

155 lbs./70 kg Shipping Weight

35" x 20" x 32" (889 x 508 x 813mm)

- **Solid Cast Iron Cylinder**
- **Start - Stop Pressure Control**
- **Fully Enclosed Belt Guard**
- **ASME/CRN Code Tank and Safety Valves**
- **Thermally Protected Electric Motor**
- **Easy to View Oil Sight Glass**
- **1/4" Regulator**
- **Durable Polyester Powder-Coated Tank**

---

**Kahlenberg Industries, Inc.**

1700 12th Street, P.O. Box 358

Two Rivers, Wisconsin, 54241

Phone: (920) 793-4507 / Fax: (920) 793-1346

Website: [www.kahlenberg.com](http://www.kahlenberg.com)

Email: [info@kahlenberg.com](mailto:info@kahlenberg.com)