

KPH Series Electric Piston Horns



- Horn construction: High strength aluminum bell (KPH-90 reinforced fiberglass) , supporting frame, aluminum crankcase, stainless steel cylinder and fasteners
- Self draining design to prevent condensation and corrosion
- Oil free, heated crankcase and piston cylinder assembly
- Motor is totally enclosed, IEEE45 marine type, IP56, insulation class F and equipped with anti-condensation strip heater

Control and Heater:	120/230V [50-60 Hz]
Power Consumption:	15 amp on 460/3/60 (other voltage available)
Operating Voltage:	460/3/60, 380/3/50 (other voltages available)
Operating Temperature:	-40°C to +45°C [-22°F to +113°F]
Finish:	Alodine Treated, Primed and Epoxy coated
Degree of Protection:	IP 56

Model Number	Vessel Length	IMO Audibility Range	Frequency	(1/3 Octave)	Basic Dimensions	Net Weight
KPH-90C	Over 200 Meters	2 Nautical Miles	90 Hz	143 dB	1518x844x949 mm (60x34x38 in)	126 kg (277 lbs)
KPH-130C	Over 75 Meters (and over 200 meters)	2 Nautical Miles	130 Hz	143 dB	999x635x845 mm (40x25x34 in)	100 kg (220 lbs)

Kahlenberg Industries, Inc.

1700 12th Street, P.O. Box 358
Two Rivers, Wisconsin, 54241
Phone: (920) 793-4507 / Fax: (920) 793-1346

Website: www.kahlenberg.com Email: info@kahlenberg.com