



REV.	BY	DATE	DESCRIPTION	APP'D.

**TECHNICAL DATA**

Frequency: 330 Hz  
 Sound Pressure Level (1/3 octave at 1 meter): 138.0 dB  
 Sound Pressure Level (dB(A) @ 1 meter): 147.5 dB

MOTOR 1.5 H.P./1.12 KW, 230/460VAC 60Hz, 3PH, 4.8/2.4 FLA, TEFC

HEATERS (3 COMBINED) 120/240 VAC, 450 TOTAL WATTS,  
 SWITCH ON AT 40°F (4°C) SWITCH OFF AT 60°F (15°C)

ELECTRICAL CONNECTIONS SHOWN ON DRWG. 3-7170

OPERATING TEMPERATURE RANGE: -40°F (-40°C) TO 140°F (60°C)  
 AIR COMPRESSOR: 1.5 HP, 1800 RPM, ROTARY VANE, OILLESS TYPE

Material: Gel Coated Fiberglass Cover, Anodized Treated Painted Aluminum Base  
 Brass Horn Driver.

Ingress protection: IP 56

⊖ = CENTER OF GRAVITY  
 Net Weight: 106 lbs, 48 kg  
 Shipping Weight: 120 lbs, kg  
 Cage Code: 75214

INTERIOR VIEW DRAWING 3-7170  
 WIRING DIAGRAM DRAWING 3-7165  
 PARTS LIST (B) DRAWING 3-7169

**CONFIDENTIAL**

INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IT IS THE PROPERTY OF KAHLBERG INDUSTRIES INC. IT IS TO BE USED SOLELY FOR THE PURPOSE PROVIDED, AND IT IS NOT TO BE DISCLOSED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF KAHLBERG INDUSTRIES INCORPORATED.



KAHLBERG INDUSTRIES INC. TWO RIVERS, WISCONSIN, 54241

**OUTLINE DIMENSIONS**  
**Z-320-SC HORN 3PH**

DR.	DATE	CKD.	SCALE	DRWG. NO.	REV.
ZJN	08/03/17	EMK	N.T.S.	3-7168	